

HD-A/B/C标准天平

HD-A/B/C standard balance

主要性能特征 CHARACTERISTIC

- 外部校准功能
External CAL Function
- 称重稳定时间可调功能
Weighing Stableness Time Adjustable
- 具有克、克拉、盎司等十种可屏蔽单位
10 Unite Shield: g, ct, lb, oz,
- 电池驱动
Battery Back Up
- 选配下挂钩称重装置
With Under Hook
- 选配内置直流可充电功能
Optional fit with inner rechargeable DC battery
- 选配RS232通讯端口连接外围设备
Fit with RS232 Line
- 选配外接显示器功能
Optional fit with extra display



HD-B

称量应用模式 APPLICATION MODE

- 百分比称重功能
Percentage Weighing Function
- 设定物体称量计数功能
Selectable Weighing and Counting Mode

主要技术指标 SPECIFICATIONS

型号 Item NO.	量程 Weighing Range(g)	可读性 Readability (g)	复性 Repeatability (g)	线性误差 Linearity (g)	操作温度范围 Surrounding (°C)	称盘尺寸 Pan Size (mm)	外形尺寸 (长*宽*高) Housing(L*W*H) (mm)	开机预热 Warm-up time (分钟/m)
HD-A60	60	0.001	±0.001	±0.002	10-36	Φ85	270*180*180	10-20
HD-A100	100							
HD-B200	200	0.01	±0.01	±0.02	10-36	Φ138	270*180*80	10-20
HD-B300	300							
HD-B500	500							
HD-B600	600							
HD-B1000	1000							
HD-B2000	2000							
HD-C1000	1000	0.1	±0.1	±0.2	10-36	Φ138	270*180*80	10-20
HD-C2000	2000							
HD-C3000	3000							
HD-C5000	5000					156*156		
HD-C6000	6000							

HP-A/B/C标准天平

HP-A/B/C standard balance

主要性能特征 CHARACTERISTIC

- 外部校准功能
External CAL Function
- 称重稳定时间可调功能
Weighing Stableness Time Adjustable
- 具有克、克拉、盎司等十种可屏蔽单位
10 Unite Shield: g, ct, lb, oz,
- 电池驱动
Battery Back Up
- 电池驱动
Battery Back Up
- 选配下挂钩称重装置
With Under Hook
- 选配内置直流可充电功能
Optional fit with inner rechargeable DC battery
- 选配RS232通讯端口连接外围设备
Fit with RS232 Line
- 选配外接显示器功能
Optional fit with extra display



HP-B

称量应用模式 APPLICATION MODE

- 百分比称重功能
Percentage Weighing Function
- 设定物体称量计数功能
Selectable Weighing and Counting Mode
- 上下限检重功能
High-low Weighing Function
- 峰值保持功能
Peak Holding Function
- 累计功能
Accumulate Function



HP-C

主要技术指标 SPECIFICATIONS

型号 Item NO.	量程 Weighing Range(g)	可读性 Readability (g)	复性 Repeatability (g)	线性误差 Linearity (g)	操作温度范围 Surrounding (°C)	称盘尺寸 Pan Size (mm)	外形尺寸 (长*宽*高) Housing(L*W*H) (mm)	开机预热 Warm-up time (分钟/m)
HP-A60	60	0.001	±0.001	0.002	10-36	Φ85	270*180*180	10-20
HP-A100	100							
HP-B200	200	0.01	±0.01	±0.02	10-36	Φ138	270*180*80	10-20
HP-B300	300							
HP-B500	500							
HP-B600	600							
HP-B1000	1000							
HP-B2000	2000							
HP-C1000	1000	0.1	±0.1	±0.2	10-36	Φ138	270*180*80	10-20
HP-C2000	2000							
HP-C3000	3000							
HP-C5000	5000					156*156		
HP-C6000	6000							